

5.10 (201) ~ 12.70 (500)	+0.03 -0.20
1.78 (070) ~ 5.09 (200)	+0.03 -0.10
0 ~ 1.77 (069)	+0.03 -0.05
DIMENSION X & Y (MILS)	TOLERANCE (MM)

13-020-84	3.84	4.50	0.4
13-020-83	2.88	3.00	0.3
13-020-82	3.67	4.00	0.4
13-020-81	4.10	4.90	0.4
13-020-80	4.50	5.70	0.4
13-020-79	4.45	5.50	0.4
13-020-78	2.18	4.85	0.2
13-020-77	3.60	3.90	0.4
13-020-76	6.46	6.20	0.4
13-020-75	6.45	6.50	0.4
13-020-74	4.10	3.90	0.4
13-020-73	5.00	5.40	0.4
13-020-72	3.50	2.50	0.3
13-020-71	2.10	4.40	0.2
13-020-70	3.60	4.40	0.4
13-020-69	3.30	4.30	0.3
13-020-68	3.20	3.50	0.3
13-020-67	2.70	3.50	0.3
13-020-66	6.50	6.60	0.4
13-020-65	5.70	5.50	0.4
13-020-64	2.30	7.00	0.2
13-020-63	2.20	7.00	0.2
13-020-62	3.42	3.62	0.3
13-020-61	5.24	4.70	0.4
13-020-60	5.90	6.30	0.4
13-020-59	6.20	4.60	0.4
13-020-58	3.90	4.50	0.4
13-020-57	4.80	5.00	0.4
PART NO.	X	Y	MAX. H

13-020-56	1.90	7.00	0.2
13-020-55	5.10	6.00	0.4
13-020-54	3.30	3.40	0.3
13-020-53	4.60	7.00	0.4
13-020-52	4.30	1.90	0.3
13-020-51	4.40	4.35	0.4
13-020-50	5.15	4.90	0.4
13-020-49	3.60	5.60	0.4
13-020-48	2.70	6.80	0.3
13-020-47	4.70	3.60	0.4
13-020-46	3.50	2.00	0.3
13-020-45	2.20	2.80	0.2
13-020-44	3.50	3.80	0.4
13-020-43	4.40	4.20	0.4
13-020-42	3.95	3.75	0.4
13-020-41	6.20	6.15	0.4
13-020-40	6.30	6.20	0.4
13-020-39	5.65	6.30	0.4
13-020-38	4.48	4.48	0.4
13-020-37	5.47	5.28	0.4
13-020-36	3.27	3.59	0.3
13-020-35	4.10	4.00	0.4
13-020-34	5.77	4.18	0.4
13-020-33	3.70	4.50	0.4
13-020-32	3.48	4.93	0.4
13-020-31	3.75	5.08	0.4
13-020-30	2.24	2.44	0.2
13-020-29	3.96	5.56	0.4
PART NO.	X	Y	MAX. H


13-020-28	2.70	5.00	0.3
13-020-27	4.24	3.70	0.4
13-020-26	4.33	4.13	0.4
13-020-25	4.30	5.20	0.4
13-020-24	4.30	3.80	0.4
13-020-23	6.50	7.00	0.4
13-020-22	4.35	4.10	0.4
13-020-21	3.81	4.83	0.4
13-020-20	4.06	4.83	0.4
13-020-19	4.95	5.00	0.4
13-020-18	6.68	7.00	0.4
13-020-17	5.20	5.76	0.4
13-020-16	5.00	4.50	0.4
13-020-15	6.64	6.64	0.4
13-020-14	5.97	5.97	0.4
13-020-13	6.87	6.87	0.4
13-020-12	6.80	5.00	0.4
13-020-11	7.00	7.00	-
13-020-10	6.00	6.00	0.4
13-020-09	5.00	7.00	0.4
13-020-08	5.00	5.00	0.4
13-020-07	4.00	6.50	0.4
13-020-06	4.00	5.25	0.4
13-020-05	4.00	4.00	0.4
13-020-04	3.50	7.00	0.3
13-020-03	3.50	5.50	0.3
13-020-02	3.50	4.50	0.3
13-020-01	3.50	3.50	0.3
PART NO.	X	Y	MAX. H

**SALES COPY
UNCONTROLLED DOCUMENT**

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED	
X.X ±0.10	GENERAL TOL. ±0.2
X.XX ±0.05	ANGLE ±0.5°
SURFACE FINISH 1.5/	
REMOVE BURRS AND SHARP EDGES	
ALL DIMENSIONS IN MM.	
13-99-027 R03	


MATERIAL: NBR



MICRO-MECHANICS PTE LTD
 mmsingapore@micro-mechanics.com
 TEL: 67468800 FAX: 67467700

PROCESS:	-
DATE:	20-2-09
DRAFTSMAN:	ANSOURI
CHECKER:	HT LEK

TITLE:	RUBBER TIP (2 SIDED CONTACTLESS) (12C HOLDER)	REV.	90
SCALE:	10:1	SHEET	1
DRAWING NO:	13-020-XX	SHEET	2



1 2 3 4 5 6

A

B

C

D

A

B

C

D


13-020-112	3.70	3.40	0.3
13-020-111	3.10	3.10	0.3
13-020-110	4.50	1.90	0.3
13-020-109	2.94	4.66	0.3
13-020-108	4.10	4.14	0.4
13-020-107	3.00	4.04	0.3
13-020-106	2.70	2.91	0.3
13-020-105	2.20	3.00	0.2
13-020-104	4.50	3.80	0.4
13-020-103	4.75	4.50	0.4
13-020-102	6.35	5.95	0.4
13-020-101	4.00	4.30	0.4
13-020-100	3.98	5.42	0.4
13-020-99	3.50	6.30	0.3
13-020-98	2.10	2.55	0.2
13-020-97	3.10	3.87	0.3
13-020-96	4.40	5.23	0.4
13-020-95	4.00	4.10	0.4
13-020-94	5.17	4.77	0.4
13-020-93	2.86	3.38	0.3
13-020-92	2.94	3.65	0.3
13-020-91	3.40	3.40	0.3
13-020-90	3.95	4.70	0.4
13-020-89	2.40	3.00	0.2
13-020-88	3.00	3.70	0.3
13-020-87	3.70	3.00	0.3
13-020-86	2.95	2.80	0.3
13-020-85	2.92	4.30	0.3
PART NO.	X	Y	MAX. H
PART NO.	X	Y	MAX. H

13-020-131	4.10	2.20	0.2
13-020-130	3.20	3.30	0.3
13-020-129	1.80	4.16	0.2
13-020-128	3.05	2.85	0.3
13-020-127	3.30	2.54	0.2
13-020-126	4.66	4.50	0.4
13-020-125	3.95	4.25	0.4
13-020-124	3.22	3.88	0.3
13-020-123	2.20	2.00	0.2
13-020-122	2.70	2.50	0.2
13-020-121	2.52	2.98	0.2
13-020-120	3.55	2.30	0.2
13-020-119	3.00	2.80	0.3
13-020-118	3.20	2.54	0.2
13-020-117	3.78	4.08	0.3
13-020-116	3.03	3.69	0.3
13-020-115	4.60	4.55	0.4
13-020-114	2.56	3.53	0.3
13-020-113	2.21	3.28	0.2
PART NO.	X	Y	MAX. H

**SALES COPY
UNCONTROLLED DOCUMENT**

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED
X.X ±0.10 GENERAL TOL. ±0.2
X.XX ±0.05 ANGLE ±0.5°
SURFACE FINISH 1.6/
REMOVE BURRS AND SHARP EDGES
ALL DIMENSIONS IN MM.

MATERIAL: NBR

MICRO-MECHANICS PTE LTD
mmsingapore@micro-mechanics.com
TEL: 67468800 FAX: 67467700

PROCESS: -
DATE: 20-2-09
DRAFTSMAN: ANSOURI
CHECKER: HT LEK

TITLE: RUBBER TIP (2 SIDED CONTACTLESS) (12C HOLDER)
SCALE: 10:1
DRAWING NO: 13-020-XX

REV. 90
SHEET 2
2

1 2 3 4 5 6