

12.71 (501) ~ 63.00 (1600)	+0.03 -0.25
5.10 (201) ~ 12.70 (500)	+0.03 -0.20
1.78 (070) ~ 5.09 (200)	+0.03 -0.10
0 ~ 1.77 (069)	+0.03 -0.05
DIMENSION A & B (MILS)	TOLERANCE (MM)

PART NO.	A (MILS)	B (MILS)	MAX. C	ØF	X	Y	HOLDER	REMARK
13-034C-38	3.67 (145)	4.67 (184)	0.4	1.0	7.0	7.0	12C	-
13-034C-37	6.40 (252)	7.50 (295)	0.4	1.0	12.0	12.0	12C	-
13-034C-36	3.20 (126)	3.37 (133)	0.3	1.0	7.0	7.0	12C	-
13-034C-35	3.56 (140)	3.56 (140)	0.4	1.0	7.0	7.0	12C	-
13-034C-34	3.20 (126)	5.00 (197)	0.3	1.0	7.0	7.0	12C	-
13-034C-33	6.09 (240)	6.98 (275)	0.4	1.0	7.0	7.0	12C	-
13-034C-32	6.35 (250)	6.60 (260)	0.4	1.0	7.0	7.0	12C	-
13-034C-31	3.30 (130)	3.80 (150)	0.3	1.0	7.0	7.0	12C	-
13-034C-30	5.84 (230)	6.35 (250)	0.4	1.0	7.0	7.0	12C	-
13-034C-29	5.00 (197)	5.50 (216)	0.4	1.0	7.0	7.0	12C	-
13-034C-28	6.70 (264)	7.00 (276)	0.4	1.0	10.0	10.0	12C	-
13-034C-27	10.16 (400)	10.16 (400)	0.4	1.0	12.0	12.0	12C	-
13-034C-26	4.83 (190)	4.83 (190)	0.4	1.0	7.0	7.0	12C	-
13-034C-25	4.06 (160)	4.06 (160)	0.4	1.0	7.0	7.0	12C	-
13-034C-24	8.00 (315)	12.00 (480)	0.4	1.0	12.0	12.0	12C	NO ANGLE FORM ON "X"
13-034C-23	9.00 (354)	11.00 (433)	0.4	1.0	12.0	12.0	12C	-
13-034C-22	15.00 (590)	15.00 (590)	0.4	2.0	18.0	18.0	12D3	-
13-034C-21	2.40 (094)	4.40 (173)	0.2	1.0	5.0	7.0	12C	-
13-034C-20	4.00 (158)	4.00 (158)	0.4	1.0	7.0	7.0	12C	-
13-034C-19	4.80 (189)	6.00 (236)	0.4	1.0	7.0	7.0	12C	-
13-034C-18	6.00 (236)	7.00 (276)	0.4	1.0	7.0	7.0	12C	NO ANGLE FORM ON "X"
13-034C-17	6.50 (256)	6.50 (256)	0.4	1.0	7.0	7.0	12C	-
13-034C-16	9.00 (354)	9.00 (354)	0.4	1.0	12.0	12.0	12C	-
13-034C-15	10.00 (394)	10.00 (394)	0.4	1.0	12.0	12.0	12C	-
13-034C-14	10.00 (394)	11.00 (433)	0.4	1.0	12.0	12.0	12C	-
13-034C-13	5.70 (224)	7.40 (291)	0.4	1.0	7.0	10.0	12C	-
13-034C-12	11.00 (433)	11.00 (433)	0.4	1.0	12.0	12.0	12C	-
13-034C-11	8.00 (315)	8.00 (315)	0.4	1.0	12.0	12.0	12C	-
13-034C-10	2.60 (102)	3.70 (145)	0.2	1.0	5.0	5.0	12C	-
13-034C-09	9.14 (359)	9.14 (359)	0.4	1.0	12.0	12.0	12C	-
13-034C-08	6.00 (236)	6.00 (236)	0.4	1.0	7.0	7.0	12C	-
13-034C-07	5.00 (197)	5.00 (197)	0.4	1.0	7.0	7.0	12C	-
13-034C-06	REFER TO 13-034K-03							
13-034C-05	6.10 (240)	6.10 (240)	0.4	1.0	7.0	7.0	12C	-
13-034C-04	8.64 (340)	9.65 (380)	0.4	1.0	12.0	12.0	12C	-
13-034C-03	5.08 (200)	7.00 (280)	0.4	1.0	7.0	7.0	12C	NO ANGLE FORM ON "X"
13-034C-02	7.62 (300)	12.00 (480)	0.4	1.0	12.0	12.0	12C	NO ANGLE FORM ON "X"
13-034C-01	8.13 (320)	12.00 (480)	0.4	1.0	12.0	12.0	12C	NO ANGLE FORM ON "X"

**SALES COPY
UNCONTROLLED DOCUMENT**


Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED
X.X ±0.10 GENERAL TOL. ±0.2
X.XX ±0.05 ANGLE ±0.5°
SURFACE FINISH 1.6/
REMOVE BURRS AND SHARP EDGES
ALL DIMENSIONS IN MM.

MATERIAL: NBR
MICRO-MECHANICS PTE LTD
mmsingapore@micro-mechanics.com
TEL: 67468800 FAX: 67467700

PROCESS: -
DATE: 15-4-09
DRAFTSMAN: DESMOND
CHECKER: JJ LOY

TITLE: RUBBER TIP	REV.:
SCALE: 10:1	1
DRAWING NO: 13-034C-XX	2



1 2 3 4 5 6

A

A

B

B

C

C

D

D

13-034C-63	2.80 (110)	3.40 (134)	0.2	1.0	5.0	5.0	12C	-
13-034C-62	6.50 (256)	8.00 (315)	0.4	1.0	12.0	12.0	12C	-
13-034C-61	5.59 (220)	12.00 (472)	0.4	1.0	12.0	7.0	12C	NO ANGLE FORM ON "X"
13-034C-60	6.80 (268)	8.68 (342)	0.4	1.0	12.0	12.0	12C	-
13-034C-59	6.89 (271)	10.06 (396)	0.4	1.0	12.0	12.0	12C	-
13-034C-58	6.54 (257)	9.32 (367)	0.4	1.0	12.0	12.0	12C	-
13-034C-57	7.75 (305)	11.29 (444)	0.4	1.0	12.0	12.0	12C	-
13-034C-56	5.51 (217)	11.12 (438)	0.4	1.0	12.0	7.0	12C	-
13-034C-55	5.22 (206)	7.53 (296)	0.4	1.0	12.0	7.0	12C	-
13-034C-54	6.43 (253)	5.99 (236)	0.4	1.0	12.0	12.0	12C	-
13-034C-53	6.80 (268)	6.80 (268)	0.4	1.0	12.0	12.0	12C	-
13-034C-52	3.30 (130)	4.32 (170)	0.2	1.0	7.0	7.0	12C	-
13-034C-51	5.00 (197)	9.00 (354)	0.4	1.0	12.0	7.0	12C	-
13-034C-50	6.80 (268)	9.00 (354)	0.4	1.0	12.0	12.0	12C	-
13-034C-49	7.80 (307)	7.80 (307)	0.4	1.0	12.0	12.0	12C	-
13-034C-48	3.00 (118)	3.70 (146)	0.3	1.0	7.0	7.0	12C	-
13-034C-47	7.00 (275)	10.00 (394)	0.4	1.0	12.0	12.0	12C	-
13-034C-46	4.75 (187)	6.75 (266)	0.4	1.0	7.0	7.0	12C	NO ANGLE FORM ON "X"
13-034C-45	4.06 (160)	8.13 (320)	0.4	1.0	12.0	7.0	12C	-
13-034C-44	2.78 (109)	3.48 (137)	0.2	1.0	7.0	7.0	12C	-
13-034C-43	REFER TO 13-034J-26							
13-034C-42	4.63 (182)	4.93 (194)	0.4	1.0	7.0	7.0	12C	-
13-034C-41	2.58 (102)	3.61 (142)	0.2	1.0	7.0	7.0	12C	-
13-034C-40	3.17 (125)	5.00 (197)	0.3	1.0	7.0	7.0	12C	-
13-034C-39	3.21 (127)	3.99 (157)	0.3	1.0	7.0	7.0	12C	-
PART NO.	A (MILS)	B (MILS)	MAX. C	ØF	X	Y	HOLDER	REMARK

**SALES COPY
UNCONTROLLED DOCUMENT**

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED	
X.X ±0.10	GENERAL TOL. ±0.2
X.XX ±0.05	ANGLE ±0.5°
SURFACE FINISH $\sqrt{16}$	
REMOVE BURRS AND SHARP EDGES	
ALL DIMENSIONS IN MM.	

MATERIAL: NBR



MICRO-MECHANICS PTE LTD
 mmsingapore@micro-mechanics.com
 TEL: 67468800 FAX: 67467700

PROCESS:	-
DATE:	15-4-09
DRAFTSMAN:	DESMOND
CHECKER:	JJ LOY

TITLE:	RUBBER TIP
SCALE:	10:1
DRAWING NO:	13-034C-XX

REV.	37
SHEET	2
	2

1 2 3 4 5 6