

SECTION X-X

NOTE:


1. 13-124-01 HAS BEEN OBSOLETE & NEW DESIGN AVAILABLE AS R7M-0025-0.

2. 13-124-02 HAS BEEN OBSOLETE & NEW DESIGN AVAILABLE AS R7M-0038-0.

13-124-12	0.50	40
13-124-11	0.30	40
13-124-10	0.41	40
13-124-07	0.33	40
13-124-06	0.25	45
13-124-05	0.46	40
13-124-03	0.64	40
13-124-02	0.38	40
13-124-01	0.25	40
PART NO.	ϕC	D^*

**SALES COPY
UNCONTROLLED DOCUMENT**

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED X.X ± 0.10 GENERAL TOL. ± 0.2 X.XX ± 0.05 ANGLE $\pm 0.5^\circ$ SURFACE FINISH $\frac{1.6}{\sqrt{R}}$ REMOVE BURRS AND SHARP EDGES ALL DIMENSIONS IN MM.	MATERIAL: NBR  MICRO-MECHANICS PTE LTD mmsingapore@micro-mechanics.com TEL: 67468800 FAX: 67467700	PROCESS: — DATE: 10-7-06 DRAFTSMAN: JASMINE CHECKER: HS TOK	TITLE: RUBBER TIP (12U1/3 HOLDER) SCALE: 10:1 DRAWING NO: 13-124-XX	REV. 19 SHEET 1 1
	<small>13-99-027 R03</small>			