



5.10 (201) ~ 12.70 (500)	+0.03 -0.20
1.78 (070) ~ 5.09 (200)	+0.03 -0.10
0 ~ 1.77 (069)	+0.03 -0.05
DIMENSION A & B (MILS)	TOLERANCE (MM)

13-182A-57	1.95 (077)	2.95 (116)	0.2
13-182A-56	2.65 (104)	2.86 (113)	0.3
13-182A-55	1.00 (039)	1.20 (047)	0.2
13-182A-54	1.40 (055)	1.80 (071)	0.2
13-182A-53	0.95 (037)	0.95 (037)	0.2
13-182A-52	1.29 (051)	1.69 (066)	0.2
13-182A-51	0.83 (032)	1.21 (048)	0.2
13-182A-50	0.97 (038)	1.14 (045)	0.2
13-182A-49	1.88 (074)	2.39 (094)	0.2
13-182A-48	0.89 (035)	1.88 (074)	0.2
13-182A-47	0.80 (031)	1.05 (041)	0.2
13-182A-46	1.30 (051)	1.95 (076)	0.2
13-182A-45	1.00 (039)	2.50 (098)	0.2
13-182A-44	1.50 (059)	3.00 (118)	0.2
13-182A-43	2.00 (079)	2.50 (098)	0.3
13-182A-42	2.70 (106)	2.70 (106)	0.2
13-182A-41	1.30 (051)	2.60 (102)	0.2
13-182A-40	1.67 (066)	1.74 (070)	0.2
13-182A-39	1.75 (069)	2.60 (102)	0.2
13-182A-38	1.60 (063)	2.20 (087)	0.2
13-182A-37	1.20 (047)	2.20 (087)	0.2
13-182A-36	1.20 (047)	1.60 (063)	0.2
13-182A-35	2.90 (114)	3.40 (133)	0.3
PART NO.	A (MILS)	B (MILS)	MAX. C

13-182A-34	0.80 (031)	0.80 (031)	0.2
13-182A-33	2.10 (083)	3.05 (120)	0.2
13-182A-32	0.90 (035)	1.90 (075)	0.2
13-182A-31	0.90 (035)	1.40 (055)	0.2
13-182A-30	0.89 (035)	0.89 (035)	0.2
13-182A-29	1.52 (060)	1.52 (060)	0.2
13-182A-28	1.27 (050)	1.27 (050)	0.2
13-182A-27	1.90 (074)	2.50 (098)	0.2
13-182A-26	2.20 (086)	3.00 (118)	0.2
13-182A-25	2.50 (098)	2.50 (098)	0.3
13-182A-24	2.10 (083)	3.40 (134)	0.3
13-182A-23	2.20 (087)	2.60 (102)	0.3
13-182A-22	2.20 (087)	2.40 (094)	0.2
13-182A-21	1.00 (039)	1.39 (055)	0.2
13-182A-20	1.15 (045)	1.15 (045)	0.2
13-182A-19	0.80 (031)	1.30 (051)	0.2
13-182A-18	1.60 (063)	2.10 (083)	0.2
13-182A-17	1.00 (039)	2.00 (079)	0.2
13-182A-16	2.29 (090)	3.80 (150)	0.2
13-182A-15	2.29 (090)	2.29 (090)	0.2
13-182A-14	1.52 (060)	2.29 (090)	0.2
13-182A-13	2.31 (091)	2.31 (091)	0.2
13-182A-12	2.10 (083)	2.60 (102)	0.2
13-182A-11	2.20 (087)	2.20 (087)	0.2
13-182A-10	1.50 (059)	1.50 (059)	0.2
13-182A-09	1.30 (051)	1.30 (051)	0.2
13-182A-08	1.33 (052)	1.96 (077)	0.2
13-182A-07	1.00 (039)	1.50 (059)	0.2
13-182A-06	2.60 (102)	2.60 (102)	0.3
13-182A-05	1.00 (039)	1.00 (039)	0.2
13-182A-04	1.40 (055)	1.40 (055)	0.2
13-182A-03	1.30 (051)	1.80 (071)	0.2
13-182A-02	3.00 (118)	3.00 (118)	0.3
13-182A-01	2.00 (079)	2.00 (079)	0.2
PART NO.	A (MILS)	B (MILS)	MAX. C

**SALES COPY
UNCONTROLLED DOCUMENT**

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

TOLERANCE UNLESS SPECIFIED
X.X ±0.10 GENERAL TOL. ±0.2
X.XX ±0.05 ANGLE ±0.5°
SURFACE FINISH 1/8
REMOVE BURRS AND SHARP EDGES
ALL DIMENSIONS IN MM.

MATERIAL: NBR (SHORE 45)
MICRO-MECHANICS PTE LTD
mmsingapore@micro-mechanics.com
TEL: 67468800 FAX: 67467700

PROCESS: -
DATE: 4-5-09
DRAFTSMAN: HS TOK
CHECKER: DESMOND

TITLE: RUBBER TIP (12U1/12U3 HOLDER)	REV. 29
SCALE: 10:1	DRAWING NO: 13-182A-XX
	SHEET 1/1